







	PROPERTY	IMPERIAL	METRIC	DESCRIPTION
PRODUCT	Fiber Type	100% Nylon	100% Nylon	100% Nylon
PROPERTIES	Fiber Mass	6600 denier	7333.33 dtex	12 Ply
	Tufted Pile Height	1.28 in.	32.512 mm	
	Colors:	Turf Green		
	Tufting Gauge	3/16 in.		
	Primary Backing	7.81 oz/yd²	221.41 g/m ²	2 Layer 13x18 Pic
	Secondary Backing	20 oz/yd²	566.99 g/m ²	Urethane
PERFORMANCE PROPERTIES	Tufted Face Weight	100 oz/yd²	2835 g/m²	ATSM D418
	Total Weight	127.81 oz/yd²	3657 g/m ²	ATSM D418
PACKAGING	Item Number			GB176
	Tufted Roll Width	15 ft.	4.57 m	

Southwest Greens International warrants to the original purchaser of the turf that for five (5) years from the date of synthetic turf installation, the turf, when installed and maintained as recommended by the yarn and turf manufacturer, will retain at least 50% of its pile fiber. If any area or portion of the turf substantially changes, as distinguished from a change in texture, or if pile heights decrease 50% or more within five years after its initial installation, Southwest Greens International will have all such areas or portions replaced with new turf of equivalent quality, excluding installation costs. Southwest Greens International also warrants that at the time of the initial turf installation, the synthetic turf will be free of manufacturing defects. Slight color changes will occur over the lifetime of this turf/carpet and is not considered an issue or basis for claim. All labor cost involved with the removal of the affected turf/carpet and reinstallation of the replacement will be the responsibility of the purchaser.

Contact Your Representative

877.260.7888

www.southwestgreens.com

^{*}For full terms, please see the 5 year warranty agreement.

^{*}Tufted pile height as standard. Pile height will draw down slightly during secondary backing process.
**Tuffing gauge and stitch rate as manufactured standard. Values will change slightly during secondary backing process.
***Standard roll lengths. Roll lengths may vary. Custom roll lengths and cuts are available upon request.
****All specifications subject to manufacturing tolerances of +/-5%.